

# Red Rubber Flange Accessory Packs

Class 125 & Class 250

## Red Rubber Ring and Full Face

| Flange Size | 1/8" Full Face Red Rubber | 1/8" Ring Type Red Rubber |
|-------------|---------------------------|---------------------------|
| 1"          | FRP-010-*                 | RRP-010-*                 |
| 1-1/4"      | FRP-012-*                 | RRP-012-*                 |
| 1-1/2"      | FRP-015-*                 | RRP-015-*                 |
| 2"          | FRP-020-*                 | RRP-020-*                 |
| 2-1/2"      | FRP-025-*                 | RRP-025-*                 |
| 3"          | FRP-030-*                 | RRP-030-*                 |
| 4"          | FRP-040-*                 | RRP-040-*                 |
| 5"          | FRP-050-*                 | RRP-050-*                 |
| 6"          | FRP-060-*                 | RRP-060-*                 |
| 8"          | FRP-080-*                 | RRP-080-*                 |
| 10"         | FRP-100-*                 | RRP-100-*                 |
| 12"         | FRP-120-*                 | RRP-120-*                 |
| 14"         | FRP-140-*                 | RRP-140-*                 |
| 16"         | FRP-160-*                 | RRP-160-*                 |
| 18"         | FRP-180-*                 | RRP-180-*                 |
| 20"         | FRP-200-*                 | RRP-200-*                 |
| 24"         | FRP-240-*                 | RRP-240-*                 |
| 30"         | FRP-300-*                 | RRP-300-*                 |
| 36"         | FRP-360-*                 | RRP-360-*                 |
| 42"         | FRP-420-*                 | RRP-420-*                 |
| 48"         | FRP-480-*                 | RRP-480-*                 |



**Red Rubber Flange Gaskets - Full Face and Ring Type to fit ANSI B16.1-Class 125 Flanges.**

**Reference Standard:** ANSI B16.1 - Flange Dimensions - Class 125

**Material Standard:** Red Rubber - ASTM D1330, Grade II, SBR/Durometer 75+/-5 Shore A/Red Color

### Heavy Hex Head Bolts and Nuts

**Reference Standard:** Heavy hex head steel bolts to ANSI B18.2.1 with heavy hex steel nuts to ANSI B18.2.2. Bolts to be threaded to ANSI B1.1 unified inch screw threads, Class 2A external & Class 2B internal.

**Material Standard:** to conform to ASTM A307 specification for carbon steel externally threaded standard fasteners, Grade B. Zinc plated - ASTM B633, Stainless Steel 304 & 316 Bolts - AASTM F593 Stainless Steel 302 & 316 Nuts - ASTM F594

\*Add suffix:

"Z" for Zinc Plated.

"304" for 304 Stainless Steel

"316" for 316 Stainless Steel

"250" for Zinc Class 250 Flange Accessories



**WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



**Napac, Inc.**  
120 Front Street, Suite 820, Worcester, MA 01608  
TEL. 800-807-2215  
Website: [www.napacinc.com](http://www.napacinc.com)

1123